

Product information

Filter series F-MI2 · Filters



Description


Filters are used in fluidic systems to protect sensitive components from damage due to contamination and particles. For the safe operation of micro annular gear pumps and their precision-machined rotors, the use of a 10 µm meshed filter is recommended. With compact filter units made out of corrosion-resistant materials, with high filtration performance and different mesh sizes, HNP Mikrosysteme offers suitable filter solutions for all of its pump series.

The filter series F-MI2 is available in three different configurations. The »inlet filter«, without an external housing, is directly immersed in the liquid. The »inline filters« are designed to be installed downstream in the feed line, i.e. directly before the pump. The maintenance-friendly »T-design« offers the advantage of changing the filter element without having to uninstall the filter from the feed line, and the option to open the bottom for releasing medium or emptying the filter. To avoid sedimentation and cross-contamination the filters have small dead volumes and are manufactured with smooth surfaces (Ra 0.8).

Advantages

- Corrosion-resistant materials
stainless steel or alloy C22, FFPM
- Metal filter elements
without solder or adhesives
- High filtration performance and small size
pleated filter elements for low pressure drops even at
high flow rates and viscosities
- Wide configuration variety
different body shapes and body materials, filter
fineness and sealing materials
- User-friendly and economical
filter elements can be cleaned or replaced

Characteristics




Technical data

Type	Inlet filter Inline filter (straight, T-shape)
Liquid temperature range	Inlet filter: -200 ... +275 °C Inline filter: -10 ... +140 °C (-40 ... +275 °C *)
Differential pressure range	Inlet filter: - Inline filter: max. 20 bar
Operating pressure	Inlet filter: - Inline filter: max. 200 bar
Seal materials	Inlet filter: - Inline filter: FPM, FFPM, EPDM
Materials	stainless steel; optional: alloy C22 (T-shape only)
Internal volume	Inlet filter: - Straight shape: 20 ml T-shape: 32 ml
Measurements (ø x H)	Inlet filter: Ø 20 x 63 mm Straight shape: Ø 32 x 86 mm T-shape: Ø 44 x 90.5 mm
Fluid connection	1/8" NPT internal thread
Filter fineness	10 µm; optional: 3 µm, 25 µm, 40 µm, 100 µm
Filter area	60 cm ²
Remarks	* depending on seal material

Notice

Even if single parameters are within the indicated performance range of technical data, certain parameter combinations may not be achievable. Single parameters may exceed their indicated performance range under adequate circumstances. For detailed evaluation please contact HNP Mikrosysteme. Actual performance may vary. Specifications are subject to change without notice.

Principle



Patents and trademarks

Micro annular gear pumps (and housings) are protected by assigned patents: EP 1 354 135 B1; US 7,698,818 B2; DE 10 2011 001 041 B4; CN 103 348 141 B; US 10,012,220 B2; CN 103 732 921 B; US 9,404,492 B2; US 6,520,757 B1.

HNPM[®], mzr[®], MoDoS[®], μ -Clamp[®], μ Dispense[®], Centrifluidic Technologies[®] are registered German trademarks of HNP Mikrosysteme GmbH.

Contact

HNP Mikrosysteme GmbH
Bleicherufer 25
19053 Schwerin
Germany

T +49 385 52190-300
F +49 385 52190-333
info@hnp-mikrosysteme.de

Last update 2019/07