

## Application questionnaire

### Customer data

company: \_\_\_\_\_  Mrs  Mr title: \_\_\_\_\_  
 \_\_\_\_\_ name: \_\_\_\_\_  
 street/no.: \_\_\_\_\_ phone: \_\_\_\_\_  
 ZIP/city: \_\_\_\_\_ fax: \_\_\_\_\_  
 country: \_\_\_\_\_ e-mail: \_\_\_\_\_

### Application

description: \_\_\_\_\_  
 \_\_\_\_\_

### Delivery data

continuous delivery  discrete dosage  
 volume flow [ml/min]: \_\_\_\_\_ volume [µl]: \_\_\_\_\_  
 tolerance of volume flow [%]: \_\_\_\_\_ tolerance of volume [%]: \_\_\_\_\_  
 dispense time [s]: \_\_\_\_\_  
 cycle time [s]: \_\_\_\_\_

### Liquid

name or CAS no.: \_\_\_\_\_ density [g/cm<sup>3</sup>]: \_\_\_\_\_  
 concentration [%]: \_\_\_\_\_ particle size [µm]: \_\_\_\_\_  
 viscosity [mPas / cP]: \_\_\_\_\_ at \_\_\_\_\_ °C solid content [vol.-%]: \_\_\_\_\_  
 liquid temperature [°C]: approx. \_\_\_\_ to \_\_\_\_ ambient temperature [°C]: approx. \_\_\_\_ to \_\_\_\_  
 pH value or range: approx. \_\_\_\_ to \_\_\_\_  
 Product info sheet / Material Safety Data Sheet:  yes\*  no

\* Please attach file

### Pressure

inlet pressure [bar]: \_\_\_\_\_ outlet pressure [bar]: \_\_\_\_\_

### Operating requirements

motor data:  24 V  three-phase 230/415 V  \_\_\_\_\_  
 control:  0-10 V  4-20 mA  RS-232  \_\_\_\_\_  
 operating hours p.a. [h/a]: \_\_\_\_\_ connecting frequency p.d. [%]: \_\_\_\_\_  
 life span [h]: \_\_\_\_\_ explosion protection ATEX: \_\_\_\_\_  
 degree of protection of enclosure: \_\_\_\_\_

### Other

Your questions / comments to us: \_\_\_\_\_  
 \_\_\_\_\_

Contact/information desired by:  telephone call  visit  quotation

### Contact

HNP Mikrosysteme GmbH  
 Bleicherufer 25 · D-19053 Schwerin

phone +49 385 52190-301  
 fax +49 385 52190-333

e-mail sales@hnp-mikrosysteme.de  
 http://www.hnp-mikrosysteme.de